

I N T O O U T



SIYATONE
BY SIYARAM

WELCOME TO

Siyatone Global Pvt Ltd

Founded in 1998, Siyatone has emerged as a pioneering force in the flooring industry. Its headquarters, advanced manufacturing facilities, and research labs are strategically located in Morbi, India.

Specializing in porcelain and ceramic tiles, Siyatone combines innovative designs with unmatched durability. Supported by **1,250 employees and 8 state-of-the-art minerals, ink, and tile production facilities**, Siyatone achieved a remarkable turnover of **\$146 million in 2023**.

As a trusted leader, Siyatone blends expertise, sustainability, and excellence to meet global demands and shape the future of the flooring industry.



SIYATONE

BY SIYARAM



More Than
110k Sq. Mtr.



27+ Year
Of Experience



More Than
1250+ Employee



5 Unit Ceramic and
3 Unit Minerals



52+ Country
Served



Worldwide
Customers

LIFE IN EVERY
CORNER

हर कोने में जिंदगी

Siyatone brings life to every corner of your space. From walls to floors, our tiles are designed to infuse vibrancy, elegance, and durability into every nook, turning houses into homes and spaces into experiences.





TRANSFORMING SPACES, BREATHING LIFE

SIYATONE
BY SIYARAM


Exploring the
magnificent glory
of surfaces

**MATT
FINISH &
LINNER & BLAST
EFFECT**







Brick Bone
45x145



Rectangle
23x48



Hexagon
48x55.4



Square
48x48





Herring Bone
73x23

**MATT
FINISH &
LINNER & BLAST
EFFECT**

SIYATONE
BY SIYARAM





Brick Bone
45x145

Rectangle
23x48



Hexagon
48x55.4

Square
48x48

Herring Bone
73x23

**MATT
FINISH &
LINNER & BLAST
EFFECT**






**MATT
FINISH &
LINNER & BLAST
EFFECT**



SIYATONE
BY SIYARAM






**MATT
FINISH &
LINNER & BLAST
EFFECT**







Brick Bone
45x145



Rectangle
23x48



Hexagon
48x55.4





Square
48x48



Herring Bone
73x23





Brick Bone
45x145

Rectangle
23x48


Hexagon
48x55.4

Square
48x48

Herring Bone
73x23

**MATT
FINISH &
LINNER & BLAST
EFFECT**







**MATT
FINISH &
LINNER & BLAST
EFFECT**

SIYATONE
BY SIYARAM






**MATT
FINISH &
LINNER & BLAST
EFFECT**


SIYATONE
BY SIYARAM







**MATT
FINISH &
LINNER & BLAST
EFFECT**





**MATT
FINISH &
LINNER & BLAST
EFFECT**






**MATT
FINISH &
LINNER & BLAST
EFFECT**

SIYATONE
BY SIYARAM






**MATT
FINISH &
LINNER & BLAST
EFFECT**

SIYATONE
BY SIYARAM








**MATT
FINISH &
LINNER & BLAST
EFFECT**

SIYATONE
BY SIYARAM







Brick Bone
45x145




Rectangle
23x48



Hexagon
48x55.4



Square
48x48




Herring Bone
73x23

**MATT
FINISH &
LINNER & BLAST
EFFECT**

SIYATONE
BY SIYARAM






**MATT
FINISH &
LINNER & BLAST
EFFECT**



SIYATONE
BY SIYARAM






**MATT
FINISH &
LINNER & BLAST
EFFECT**





**MATT
FINISH &
LINNER & BLAST
EFFECT**






**MATT
FINISH &
LINNER & BLAST
EFFECT**

SIYATONE
BY SIYARAM



Technical Features



**Wide Range of
Colors, Sizes,
Thicknesses & Finishes**

The surfaces are available in a wide variety to fit in all types of spaces.




**Hygienic
Surfaces**

Fully safe and compatible with food. It is very easy to clean.




**Easy to
Clean**

No special cleaning products required.



**Unalterable
Colours**

Without any organic pigment, the color of the surfaces can resist UV radiation and extreme climatic conditions.




**Heat
Resistant**

The surfaces are made of high-temperature resistant material.



**Chemical
Resistant**

The surfaces are resistant to detergents and disinfectants.




**Breaking
Strength**

It's thinness provides great resistance to bending.



**Environment
Friendly**

100% Natural. These surfaces do not release any substances, also it can be easily milled and recycled.



**Stain
Resistant**


The surfaces do not stain when in contact with acids such as lemon or with cleaning products such as bleach or ammonia.




**Frost
Resistant**

The surfaces are resistant to frost.


Tiles Laying Instructions




The substrate to be tiled must be perfectly leveled. We recommend that damp areas be waterproofed before hand and the levelling in the adhesive layer must be uniform to prevent the emergence of tile edges.




For better bonding strength of the adhesive, we recommend first cleaning the surface to be tiled.




The type of adhesive to be used is determined by the properties of the substrate to be tiled, as well as the type of the chosen ceramic tile, the tile format and the end use.




The thin-bed installation method is recommended with a flexible adhesive. For 3+ mm pieces with a glass fibre base, the buttering-floating technique is recommended, paying special attention to fully covering the corners.



Careful handling is advisable to prevent nipped edges, chipping or scratches on the tile surface.




The separation between pieces must be more than 1.5 mm. The cross-spacers to be used must be at least 1 mm.




We recommend that you compensate the levelling for any possible movement or contraction of already-installed material. This procedure will prevent most minor differences in levels.



We recommend that you consider the inclusion of perimeter joints, which will help absorb any movements after installation. If the substrate already has structural joints or dividing joints, these must be respected when ceramic tiles are installed.



The installation joints must be empty and free of bonding materials and traces of dirt and grime. In this way, the adhesion of the grout will be improved and will be more effective.



When laying floor coverings, and once the ceramic tile is laid, we recommend that you protect the surface until the building project is complete. Following this procedure will safeguard the material and will make cleaning easier.

TECHNICAL SPECIFICATION

Sr. No.	CHARACTERISTICE	STANDARD AS PER IS 15622:2006 GROUP BIA	MEAN VALUE OF OUR VITRIFIED TILES
1	Deviation in Length & Width	± 0.6%	± 0.4%
2	Deviation In Thickness	± 0.5%	± 0.4%
3	Straightness of Sides	± 0.5%	± 0.4%
4	Rectrangularity	± 0.6%	± 0.5%
5	Surface Flatness	± 0.5%	± 0.5%
6	Hardness on Mohs Scale	> 6	> 7
7	Water Absorption	< 0.5%	≤ 0.05%
8	Flexural Strength (Mor)	> 35 N/mm²	> 40 N/mm²
9	Abrasion Resistance	< 175 N/mm²	< 145 N/mm²
10	Sjid Resistaance	> 0.4	> 0.4
11	Bulk Density	> 2	> 2.4
12	Crost Resistance	Frost Proof	Frost Proof
13	Chemical Resistance	No Damage	No Damage
14	Thermal Shock Resistance	No Damage	No Damage
15	Thermal Expansion	< 9x10	< 6x10
16	Stain Resistance	Resistance	Resistance
17	Moisture Expansion	Nill	Nill
18	Glossiness	Gloss Meter	Min. 90 reflection
19	Breaking Strength	1300 N	2000 N


PACKING DETAILS

Sr. No.	Size	Piece Per Box	Sq. mtr.	Sq. ft.
01	600x1200mm	2	1.44	15.50

A MARK OF
NATURE
&
DURABILITY



RIBBON SERIES



Available in
600x1200mm

Available Punch
600x1200mm
Matt | Blast | Liner



Thank You



SIYATONE GLOBAL PVT LTD

Regd.Office : Survey No. 105/1 P2,
Opp. Intel Vitrified, Jambudiya,
Morbi - 363 642.

CIN : U46909GJ2024PTC156431

Call on : +91 75740 74011
Email : info@siyatone.com